

View Online at <https://aerobasegroup.com/nsn/5910-00-667-5824>

Body Style:

Rotary

Body Length:

0.750 inches

Body Width:

0.531 inches

Body Height:

0.234 inches

Temperature Coefficient Of Capacitance In Ppm Per Deg Celsius:

0.0 single section

Unthreaded Mounting Hole Diameter:

0.124 inches and 0.124 inches

Dissipation Factor At 25 Deg Celsius In Percent:

0.2

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

0.312 inches

Inclosure Type:

Encapsulated

Adjustment Device Rotation:

360.0 degrees clockwise

Insulation Dc Resistance At 25 Deg Celsius:

10000.0 megohms

Mounting Facility Type And Quantity:

2 unthreaded hole

Nonderated Operating Temp:

Between -55.0 degrees celsius and 85.0 degrees celsius

Capacitance Range In Picofarads:

+5.0 to 37.0 single section

Nonderated Voltage Rating And Type:

350.0 dc continuous single section

Capacitance Change In Percent At Operating Temperature From 25 Deg Celsius:

-4.50 to 2.00 first section

Adjustment Device Drive Type And Quantity:

1 slotted screw

Capacitance Drift In Picofarads:

0.50 single section

Material:

Plastic phenolic base

Terminal Type And Quantity:

2 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A096a0