NSN 5910-00-667-6774

Glass Dielectric Variable Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-667-6774 **Thread Class:** 2a **Body Style:** Piston **Bushing Diameter:** 0.250 inches First Flat Length: Any acceptable single shaft **Shaft Diameter:** 0.073 inches single shaft **Bushing Length:** 0.250 inches **Shaft Length:** 0.375 inches single shaft **Body Length:** 1.000 inches **Overall Diameter:** 0.312 inches Tempurature Coefficient Of Capacitance In Ppm Per Deg Celsius: 50.0 single section **Tolerance Of Tempurature Coefficient In Ppm Per Deg Celsius:** -50.0 to 50.0 single section **Square Shaft Width:** Any acceptable single shaft **Mounting Facility Screw Thread Series Designator:** Unef **Inclosure Type:** Encased **Adjustment Device Torque:** Between 2.000 inch-ounces and 14.000 inch-ounces **Bushing Shape:** Round w/flat Insulation Dc Resistance At 25 Deg Celsius: 10.0 gigohms **Bushing Width:** 0.230 inches **Mounting Facility Type And Quantity:** 1 threaded bushing **Nonderated Operating Temp:** Between -55.0 degrees celsius and 85.0 degrees celsius

Thread Size:

0.250 inches

NSN 5910-00-667-6774

Glass Dielectric Variable Capacitor - Page 2 of 2



Shaft Type:
Round, square single shaft
Capacitance Range In Picofarads:
+1.0 to 7.5 single section
Nonderated Voltage Rating And Type:
100.0 dc continuous single section
Adjustment Device Drive Type And Quantity:
1 shaft
Terminal Type And Quantity:
1 wire lead
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A096a0