NSN 5910-00-667-7063

Paper Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-667-7063

	3
Body Style	e:
W/o mtg fa	cilities, axial terminals
Reliability	Indicator:
Not establi	shed
Terminal L	ength:
1.625 inche	es
Body Dian	neter:
0.375 inche	es
Body Leng	gth:
0.938 inche	es
Body Widt	th:
0.375 inche	es
Body Heig	ıht:
0.375 inche	es
Terminal [Diameter:
0.032 inche	es
Schematic	c Diagram Designator:
No commo	n or grounded electrode (s)
Internal El	ectrical Connection Type:
Inserted ta	b
Features F	Provided:
Hermetical	ly sealed case
Insulation	Resistance At Maximum Operating Temp:
20.0 mego	hm-microfarads
Capacitan	ce Value Per Section:
68000.000	picofarads single section
Nonderate	ed Operating Temp:
Between -5	55.0 degrees celsius and 85.0 degrees celsius
Nonderate	ed Continuous Voltage Rating And Type Per Section:
200.0 dc si	ngle section
Tolerance	Range Per Section:
-20.00 to 2	0.00 percent single section
Case Mate	erial:
Metal	
Insulation	Resistance At Reference Temp:
6000.0 me	gohms
Dissipatio	n Factor At Reference Tempurature In Percent:
1.0000	
Terminal S	Surface Treatment:
Solder	

Plastic

Case Insulation Material:

NSN 5910-00-667-7063

Paper Dielectric Fixed Capacitor - Page 2 of 2



Test Data Document:

81349-mil-c-25 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

2 uninsulated wire lead

Specification Data:

81349-mil-c-25/1e government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0