Paper Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-668-0584

Body Style:

W/o mtg facilities, terminals on opposite surfaces

Reliability Indicator:

Not established

Terminal Length:

1.250 inches

Body Length:

0.812 inches

Body Width:

0.219 inches

Body Height:

0.531 inches

Schematic Diagram Designator:

No common or grounded electrode (s)

Internal Electrical Connection Type:

Extended foil

Insulation Resistance At Maximum Operating Temp:

600.0 megohm-microfarads

Capacitance Value Per Section:

10000.000 picofarads single section

Nonderated Operating Temp:

Between -55.0 degrees celsius and 85.0 degrees celsius

Nonderated Continuous Voltage Rating And Type Per Section:

300.0 dc single section

Tolerance Range Per Section:

-20.00 to 20.00 percent single section

Case Material:

Plastic

Insulation Resistance At Reference Temp:

6000.0 megohm-microfarads

Dissipation Factor At Reference Tempurature In Percent:

0.8000

Test Data Document:

81349-mil-c-91 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

2 uninsulated wire lead

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

NSN 5910-00-668-0584

Paper Dielectric Fixed Capacitor - Page 2 of 2

Fiig: A010b0

