NSN 5910-00-668-1239

Glass Dielectric Variable Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-668-1239 **Thread Class:** 2a **Body Style:** Piston **Bushing Diameter:** 0.257 inches **Shaft Diameter:** 0.188 inches single shaft **Bushing Length:** 0.250 inches **Shaft Length:** 1.312 inches single shaft **Body Length:** 2.562 inches **Overall Diameter:** 0.375 inches **Quality Factor At 25 Deg Celsius:** 500.0 **Mounting Facility Screw Thread Series Designator:** Unf **Inclosure Type:** Encased **Adjustment Device Torque:** Between 2.000 inch-ounces and 4.000 inch-ounces **Bushing Shape:** Round w/flat Insulation Dc Resistance At 25 Deg Celsius: 1000.0 gigohms **Bushing Width:** 0.237 inches **Mounting Facility Type And Quantity:** 1 threaded bushing **Nonderated Operating Temp:** Between -55.0 degrees celsius and 125.0 degrees celsius **Thread Size:** 0.250 inches **Shaft Type:** Round, slotted single shaft Capacitance Range In Picofarads:

+5.0/+45.0 single section

Nonderated Voltage Rating And Type:

1000.0 dc continuous single section

NSN 5910-00-668-1239

Glass Dielectric Variable Capacitor - Page 2 of 2



| Adjustment Device Drive Type And Quantity: |
|--|
| 1 shaft |
| Terminal Type And Quantity: |
| 1 wire lead |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |

A096a0