NSN 5910-00-668-3163

Air Dielectric Variable Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-668-3163 **Thread Class:** 2a **Body Style:** Plate-meshing **Overall Length:** 1.312 inches **Bushing Diameter:** 0.250 inches **Overall Height:** 0.750 inches **Overall Width:** 0.625 inches **Shaft Diameter:** 0.188 inches single shaft **Bushing Length:** 0.562 inches **Shaft Length:** 0.500 inches single shaft **Body Length:** 0.812 inches Tempurature Coefficient Of Capacitance In Ppm Per Deg Celsius: 50.0 single section **Quality Factor At 25 Deg Celsius:** 1500.0 **Mounting Facility Screw Thread Series Designator:** Unef **Inclosure Type:** Uninclosed **Tuning Characteristic:** Straight line capacity single section **Split-stator Rotary Plate Type:** Butterfly **Adjustment Device Rotation:** 90.0 degrees clockwise **Adjustment Device Torque:** Between 1.500 inch-ounces and 6.000 inch-ounces **Bushing Shape:** Round w/double flat Insulation Dc Resistance At 25 Deg Celsius: 10.0 gigohms

Bushing Width: 0.187 inches

NSN 5910-00-668-3163

Air Dielectric Variable Capacitor - Page 2 of 2



Mounting Facility Type And Quantity:
1 threaded bushing
Thread Size:
0.250 inches
Shaft Type:
Round, slotted single shaft
Capacitance Range In Picofarads:
+2.1/+4.5 single section
Nonderated Voltage Rating And Type:
1250.0 ac peak single section
Adjustment Device Drive Type And Quantity:
1 shaft
Terminal Type And Quantity:
3 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig: