Paper Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-668-8102

## Body Style:

W/thd mtg studs, axial terminals

### **Reliability Indicator:**

Not established

### **Terminal Length:**

1.625 inches

## Body Diameter:

0.670 inches

### Body Length:

1.624 inches

# Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

0.875 inches

## Schematic Diagram Designator:

No common or grounded electrode (s)

# Internal Electrical Connection Type:

Extended foil

### Mounting Facility Screw Thread Series Designator:

Unc

### Mounting Facility Type And Quantity:

2 threaded mounting studs

### **Features Provided:**

Hermetically sealed case

#### Insulation Resistance At Maximum Operating Temp:

10.0 megohm-microfarads

#### Capacitance Value Per Section:

1.000 microfarads single section

#### Nonderated Operating Temp:

Between -55.0 degrees celsius and 125.0 degrees celsius

#### Thread Size:

0.138 inches

#### Nonderated Continuous Voltage Rating And Type Per Section:

100.0 dc single section

#### **Tolerance Range Per Section:**

-5.00 to 5.00 percent single section

#### Case Material:

Metal

#### Insulation Resistance At Reference Temp:

20000.0 megohm-microfarads

#### Dissipation Factor At Reference Tempurature In Percent:

1.0000

#### **Terminal Surface Treatment:**

Solder



### Terminal Type And Quantity:

2 uninsulated wire lead

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A010b0