

View Online at <https://aerobasegroup.com/nsn/5910-00-669-0797>

Body Style:

W/mtg bracket, terminals on opposite ends

Reliability Indicator:

Not established

Terminal Length:

1.000 inches

Body Diameter:

0.438 inches

Body Length:

0.938 inches

Body Width:

1.219 inches

Body Height:

0.438 inches

Continuous Current Rating In Amps:

5.0

Terminal Diameter:

0.138 inches

Unthreaded Mounting Hole Diameter:

0.154 inches

Center To Center Distance Between Mounting Facilities Parallel To Diameter:

0.938 inches

Schematic Diagram Designator:

Feedthrough

Mounting Facility Type And Quantity:

2 unthreaded mounting holes

Features Provided:

Hermetically sealed case

Capacitance Value Per Section:

10000.000 picofarads single section

Nonderated Operating Temp:

Between -55.0 degrees celsius and 85.0 degrees celsius

Nonderated Continuous Voltage Rating And Type Per Section:

250.0 ac-rms single section

Tolerance Range Per Section:

-10.00 to 20.00 percent single section

Case Material:

Metal

Dissipation Factor At Reference Temperature In Percent:

1.0000

Test Data Document:

81349-mil-c-11693 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

2 threaded stud

Specification Data:

81349-mil-c-11693/8 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0