## NSN 5910-00-669-4926

Paper Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-669-4926

**Body Style:** 

W/o mtg facilities, terminal (s) on one surface

Reliability Indicator:

Not established

**Unable To Decode:** 

Unable to decode and unable to decode

**Unable To Decode:** 

Unable to decode and unable to decode

**Unable To Decode:** 

Unable to decode and unable to decode

**Body Length:** 

Between 3.687 inches and 3.813 inches

**Body Width:** 

Between 1.697 inches and 1.813 inches

**Body Height:** 

Between 3.936 inches and 4.063 inches

**Center To Center Distance Between Terminals Parallel To Length:** 

1.663 inches

**Terminal Diameter:** 

0.190 inches

**Terminal Height From Body:** 

3.500 inches

**Schematic Diagram Designator:** 

No common or grounded electrode (s)

**Internal Electrical Connection Type:** 

Extended foil

**Features Provided:** 

Hermetically sealed case

**Capacitance Value Per Section:** 

0.0025 microfarads single section

**Nonderated Operating Temp:** 

Between -55.0 degrees celsius and 85.0 degrees celsius

Nonderated Continuous Voltage Rating And Type Per Section:

9000.0 dc single section

**Tolerance Range Per Section:** 

-10.00 to 10.00 percent single section

**Case Material:** 

Metal

**Insulation Resistance At Reference Temp:** 

10000.0 megohms

**Dissipation Factor At Reference Tempurature In Percent:** 

0.005

NSN 5910-00-669-4926 Paper Dielectric Fixed Capacitor - Page 2 of 2



Power Factor At Reference Tempurature In Percent:
0.005
Case Insulation Material:
Plastic
Terminal Type And Quantity:
2 standoff, threaded stud
Shelf Life:
N/a
Unit Of Measure:
<del>.</del>
Demilitarization:
No

Fiig: A010b0