NSN 5910-00-669-4926

Paper Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-669-4926

Body Style:

W/o mtg facilities, terminal (s) on one surface

Reliability Indicator:

Not established

Unable To Decode:

Unable to decode and unable to decode

Unable To Decode:

Unable to decode and unable to decode

Unable To Decode:

Unable to decode and unable to decode

Body Length:

Between 3.687 inches and 3.813 inches

Body Width:

Between 1.697 inches and 1.813 inches

Body Height:

Between 3.936 inches and 4.063 inches

Center To Center Distance Between Terminals Parallel To Length:

1.663 inches

Terminal Diameter:

0.190 inches

Terminal Height From Body:

3.500 inches

Schematic Diagram Designator:

No common or grounded electrode (s)

Internal Electrical Connection Type:

Extended foil

Features Provided:

Hermetically sealed case

Capacitance Value Per Section:

0.0025 microfarads single section

Nonderated Operating Temp:

Between -55.0 degrees celsius and 85.0 degrees celsius

Nonderated Continuous Voltage Rating And Type Per Section:

9000.0 dc single section

Tolerance Range Per Section:

-10.00 to 10.00 percent single section

Case Material:

Metal

Insulation Resistance At Reference Temp:

10000.0 megohms

Dissipation Factor At Reference Tempurature In Percent:

0.005

NSN 5910-00-669-4926 Paper Dielectric Fixed Capacitor - Page 2 of 2



| Power Factor At Reference Tempurature In Percent: |
|---|
| 0.005 |
| Case Insulation Material: |
| Plastic |
| Terminal Type And Quantity: |
| 2 standoff, threaded stud |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| . |
| Demilitarization: |
| No |

Fiig: A010b0