

View Online at https://aerobasegroup.com/nsn/5910-00-681-2116

#### **Body Style:**

W/o mtg facilities, axial terminals

#### **Reliability Indicator:**

Not established

## **Terminal Length:**

1.250 inches

#### **Body Diameter:**

0.225 inches

**Body Length:** 

0.762 inches

#### Schematic Diagram Designator:

No common or grounded electrode (s)

#### **Capacitance Value Per Section:**

100.000 picofarads single section

#### Nonderated Operating Temp:

Between -55.0 degrees celsius and 125.0 degrees celsius

## Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius:

-330.0 single section

### Nonderated Continuous Voltage Rating And Type Per Section:

500.0 dc single section

#### **Tolerance Range Per Section:**

-10.00/+10.00 percent single section

### **Case Material:**

Ceramic

#### Insulation Resistance At Reference Temp:

7500.0 megohms

#### **Quality Factor At Reference Temp:**

1000.0000

## **Terminal Surface Treatment:**

Solder

## Test Data Document:

81349-milc20 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

# Terminal Type And Quantity:

2 uninsulated wire lead

Shelf Life:

N/a

Unit Of Measure:

--

## Demilitarization:

No

Fiig:

A010b0