Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-681-2410

### Body Style:

W/thd bushing mtg, terminals on opposite ends

**Reliability Indicator:** 

Not established

**Terminal Length:** 

0.296 inches

#### **Body Diameter:**

0.562 inches

**Body Length:** 

1.062 inches

#### Schematic Diagram Designator:

No common or grounded electrode (s)

#### Mounting Facility Screw Thread Series Designator:

Unf

#### Mounting Facility Type And Quantity:

1 threaded bushing

## Features Provided:

Hermetically sealed case

### Insulation Resistance At Maximum Operating Temp:

10.0 megohm-microfarads

### **Capacitance Value Per Section:**

1.000 microfarads single section

#### Nonderated Operating Temp:

Between -55.0 degrees celsius and 125.0 degrees celsius

#### **Thread Size:**

0.312 inches

#### Nonderated Continuous Voltage Rating And Type Per Section:

200.0 dc single section

#### **Tolerance Range Per Section:**

-10.00/+10.00 percent single section

#### **Case Material:**

Metal

### Insulation Resistance At Reference Temp:

2000.0 megohm-microfarads

# Power Factor At Reference Tempurature In Percent:

1.0000

### **Case Insulation Material:**

Plastic

#### **Terminal Type And Quantity:**

2 tab, solder lug

Shelf Life:

N/a



Unit Of Measure:

---

Demilitarization:

No

Fiig:

A010b0