NSN 5910-00-681-6580



Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5910-00-681-6580

| view Offilitie at https://aerobasegroup.com/hsh/os/10-00-001-0000 |
|--|
| Body Style: |
| W/o mtg facilities, axial terminals |
| Reliability Indicator: |
| Not established |
| Terminal Length: |
| 1.625 inches |
| Body Diameter: |
| 0.500 inches |
| Body Length: |
| 1.062 inches |
| Terminal Diameter: |
| 0.032 inches |
| Schematic Diagram Designator: |
| Electrod (s) grounded to case, w/gnd terminal |
| Features Provided: |
| Hermetically sealed case |
| Capacitance Value Per Section: |
| 0.220 microfarads single section |
| Nonderated Operating Temp: |
| Between -55.0 degrees celsius and 100.0 degrees celsius |
| Nonderated Continuous Voltage Rating And Type Per Section: |
| 400.0 dc single section |
| Tolerance Range Per Section: |
| -20.00/+20.00 percent single section |
| Case Material: |
| Metal |
| Dissipation Factor At Reference Tempurature In Percent: |
| 1.0000 |
| Terminal Surface Treatment: |
| Solder |
| Test Data Document: |
| 81349-mil-c-18312 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification |
| format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain |
| environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). |
| Terminal Type And Quantity: |
| 2 uninsulated wire lead |
| Specification Data: |
| 81349-mil-c-18312b government specification |
| Shelf Life: |
| N/a |
| Unit Of Measure: |

No

Demilitarization:

NSN 5910-00-681-6580

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 2 of 2



Fiig:

A010b0