

View Online at <https://aerobasegroup.com/nsn/5910-00-681-6587>

**Body Style:**

W/mtg tabs/flanges, terminal (s) on one surface

**Reliability Indicator:**

Not established

**Body Length:**

2.281 inches

**Body Width:**

1.266 inches

**Body Height:**

1.781 inches

**Maximum Rf Current Rating At Highest Rated Frequency In Rms Amps:**

3.75

**Highest Frequency At Which Rf Current Rating Applies In KiloHertz:**

3000.0

**Maximum Rf Current Rating At Lowest Rated Frequency In Rms Amps:**

0.9

**Lowest Frequency At Which Rf Current Rating Applies In KiloHertz:**

100.0

**Unthreaded Mounting Hole Diameter:**

0.180 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:**

2.625 inches

**Schematic Diagram Designator:**

No common or grounded electrode (s)

**Mounting Facility Type And Quantity:**

1 unthreaded mounting holes

**Insulation Resistance At Maximum Operating Temp:**

2000.0 megohms

**Capacitance Value Per Section:**

2000.000 picofarads single section

**Nonderated Operating Temp:**

Between -55.0 degrees celsius and 70.0 degrees celsius

**Nonderated Continuous Voltage Rating And Type Per Section:**

5000.0 dc single section

**Tempurature Coefficient Of Capacitance Range Per Section In Ppm Per Deg Celsius:**

+0.0 to 70.0 single section

**Tolerance Range Per Section:**

-5.00 to 5.00 percent single section

**Case Material:**

Plastic

**Insulation Resistance At Reference Temp:**

7500.0 megohms

**Terminal Type And Quantity:**

2 threaded stud

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A010b0