

View Online at <https://aerobasegroup.com/nsn/5910-00-681-6587>

Body Style:

W/mtg tabs/flanges, terminal (s) on one surface

Reliability Indicator:

Not established

Body Length:

2.281 inches

Body Width:

1.266 inches

Body Height:

1.781 inches

Maximum Rf Current Rating At Highest Rated Frequency In Rms Amps:

3.75

Highest Frequency At Which Rf Current Rating Applies In KiloHertz:

3000.0

Maximum Rf Current Rating At Lowest Rated Frequency In Rms Amps:

0.9

Lowest Frequency At Which Rf Current Rating Applies In KiloHertz:

100.0

Unthreaded Mounting Hole Diameter:

0.180 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

2.625 inches

Schematic Diagram Designator:

No common or grounded electrode (s)

Mounting Facility Type And Quantity:

1 unthreaded mounting holes

Insulation Resistance At Maximum Operating Temp:

2000.0 megohms

Capacitance Value Per Section:

2000.000 picofarads single section

Nonderated Operating Temp:

Between -55.0 degrees celsius and 70.0 degrees celsius

Nonderated Continuous Voltage Rating And Type Per Section:

5000.0 dc single section

Tempurature Coefficient Of Capacitance Range Per Section In Ppm Per Deg Celsius:

+0.0 to 70.0 single section

Tolerance Range Per Section:

-5.00 to 5.00 percent single section

Case Material:

Plastic

Insulation Resistance At Reference Temp:

7500.0 megohms

Terminal Type And Quantity:

2 threaded stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0