

View Online at <https://aerobasegroup.com/nsn/5910-00-681-9204>

Thread Class:

2a

Body Style:

Plate-meshing

Overall Length:

1.203 inches

Bushing Diameter:

0.266 inches

Overall Height:

0.750 inches

Overall Width:

0.625 inches

Shaft Diameter:

0.188 inches single shaft

Bushing Length:

0.250 inches

Shaft Length:

0.500 inches single shaft

Body Length:

0.703 inches

Quality Factor At 25 Deg Celsius:

1500.0

Fragility Factor:

Moderately rugged

Mounting Facility Screw Thread Series Designator:

Unef

Inclosure Type:

Uninclosed

Plate Quantity:

5

Tuning Characteristic:

Straight line capacity single section

Split-stator Rotary Plate Type:

Butterfly

Adjustment Device Torque:

Between 2.500 inch-ounces and 10.000 inch-ounces

Bushing Shape:

Round w/flat

Plate Air Gap:

0.010 inches

Bushing Width:

0.203 inches

Mounting Facility Type And Quantity:

1 threaded bushing

Nonderated Operating Temp:

Between -55.0 degrees celsius and 85.0 degrees celsius

Thread Size:

0.250 inches

Shaft Type:

Round, slotted single shaft

Capacitance Range In Picofarads:

+1.3/+5.4 single section

Nonderated Voltage Rating And Type:

880.0 ac peak single section

Adjustment Device Drive Type And Quantity:

1 shaft

Material:

Steatite base

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A096a0