## NSN 5910-00-682-3237

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-682-3237				
Body Style:				
W/mtg bracket, axial terminals				
Reliability Indicator:				
Not established				
Terminal Length:				
0.296 inches				
Body Diameter:				
1.000 inches				
Body Length:				
2.624 inches				
Unthreaded Mounting Hole Diameter:				
0.156 inches				
Schematic Diagram Designator:				
No common or grounded electrode (s)				
Mounting Facility Type And Quantity:				
1 unthreaded mounting holes				
Features Provided:				
Hermetically sealed case				
Insulation Resistance At Maximum Operating Temp:				
10.0 megohm-microfarads				
Capacitance Value Per Section:				
12.000 microfarads single section				
Nonderated Operating Temp:				
Between -55.0 degrees celsius and 125.0 degrees celsius				
Nonderated Continuous Voltage Rating And Type Per Section:				
200.0 dc single section				
Tolerance Range Per Section:				
-10.00/+10.00 percent single section				
Case Material:				
Metal				
Insulation Resistance At Reference Temp:				
2000.0 megohm-microfarads				
Power Factor At Reference Tempurature In Percent:				
1.0000				
Terminal Surface Treatment:				
Solder				
Case Insulation Material:				
Plastic				
Terminal Type And Quantity:				
2 tab, solder lug				
Shelf Life:				

N/a

## NSN 5910-00-682-3237

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 2 of 2



	١	:4	<b>^</b> 4	Maaa
L	JΠ	Iτ	OI.	Measure:

--

Demilitarization:

No

Fiig:

A010b0