## NSN 5910-00-682-3681

**Body Style:** 

W/o mtg facilities, axial terminals

Paper Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-682-3681

**Reliability Indicator:** Not established **Terminal Length:** 1.500 inches **Body Diameter:** 0.625 inches **Body Length:** 1.375 inches **Body Width:** 0.625 inches **Body Height:** 0.625 inches **Terminal Diameter:** 0.032 inches **Schematic Diagram Designator:** Electrod (s) grounded to case, w/gnd terminal **Internal Electrical Connection Type:** Inserted tab **Features Provided:** Hermetically sealed case **Insulation Resistance At Maximum Operating Temp:** 20.0 megohm-microfarads **Capacitance Value Per Section:** 50000.000 picofarads single section **Nonderated Operating Temp:** Between -55.0 degrees celsius and 85.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 600.0 dc single section **Tolerance Range Per Section:** -10.00 to 10.00 percent single section **Insulation Resistance At Reference Temp:** 6000.0 megohms **Dissipation Factor At Reference Tempurature In Percent:** 1.0000

81349-mil-c-25 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental

and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## **Terminal Type And Quantity:**

**Terminal Surface Treatment:** 

Solder

2 uninsulated wire lead

**Test Data Document:** 

## NSN 5910-00-682-3681

Paper Dielectric Fixed Capacitor - Page 2 of 2



Specification Data	Spe	ecifica	ition	Data:
--------------------	-----	---------	-------	-------

81349-mil-c-25/2b government specification

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A010b0