

View Online at https://aerobasegroup.com/nsn/5910-00-682-3708

Body Style:

W/o mtg facilities, axial terminals

Reliability Indicator:

Not established

Terminal Length:

1.500 inches

Body Diameter:

0.400 inches

Body Length:

1.124 inches

Schematic Diagram Designator:

Electrod (s) grounded to case, w/gnd terminal

Internal Electrical Connection Type:

Extended foil

Features Provided:

Hermetically sealed case

Insulation Resistance At Maximum Operating Temp:

40000.0 megohm-microfarads

Capacitance Value Per Section:

15000.000 picofarads single section

Nonderated Operating Temp:

Between -55.0 degrees celsius and 85.0 degrees celsius

Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius:

-120.0 single section

Nonderated Continuous Voltage Rating And Type Per Section:

100.0 dc single section

Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius:

-50.0/+50.0 single section

Tolerance Range Per Section:

-20.00/+20.00 percent single section

Case Material:

Metal

Insulation Resistance At Reference Temp:

250000.0 megohm-microfarads

Dissipation Factor At Reference Tempurature In Percent:

0.1000

Terminal Surface Treatment:

Solder

Dielectric Material:

Plastic polystyrene

Terminal Type And Quantity:

2 uninsulated wire lead

Plastic Dielectric Fixed Capacitor - Page 2 of 2



Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0