

View Online at <https://aerobasegroup.com/nsn/5910-00-682-3791>

Body Style:

W/o mtg facilities, radial terminals

Reliability Indicator:

Not established

Terminal Length:

1.500 inches

Body Diameter:

0.750 inches

Body Length:

0.156 inches

Center To Center Distance Between Terminals Parallel To Diameter:

0.380 inches

Terminal Diameter:

0.025 inches

Schematic Diagram Designator:

No common or grounded electrode (s)

End Application:

Virginia class cgn (41); los angeles class ssn (688); spruance class dd (963); forrestal class cv; sturgeon class ssn (637); ticonderoga class cg (47); powhatan class t-atf 166; kidd class ddg; arleigh burke class ddg; nimitz class cvn

Capacitance Value Per Section:

20000.000 picofarads single section

Voltage Temperature Limits Per Section In Percent Capacitance Change:

-56.0/+22.0 with rated voltage applied single section

Nonderated Operating Temp:

Between 10.0 degrees celsius and 85.0 degrees celsius

Nonderated Continuous Voltage Rating And Type Per Section:

500.0 dc single section

Criticality Code Justification:

Feat

Tolerance Range Per Section:

-20.00/+20.00 percent single section

Case Material:

Plastic

Terminal Surface Treatment:

Solder

Special Features:

Weapon system essential

Terminal Type And Quantity:

2 uninsulated wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A010b0