NSN 5910-00-683-3049

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-683-3049
Body Style:
W/o mtg facilities, axial terminals
Reliability Indicator:
Not established
Terminal Length:
1.500 inches
Body Diameter:
0.281 inches
Body Length:
0.875 inches
Schematic Diagram Designator:
No common or grounded electrode (s)
Anode Type:
Plain foil
Impedance At Minimum Operating Tempurature In Ohms:
1485.0
Electrical Polarization:
Nonpolarized
Features Provided:
Hermetically sealed case
Capacitance Value Per Section:
1.500 microfarads single section
Nonderated Operating Temp:
Between -55.0 degrees celsius and 85.0 degrees celsius
Dc Leakage At Maximum Operating Temp:
16.0 milliamperes
Nonderated Continuous Voltage Rating And Type Per Section:
100.0 dc single section
Tolerance Range Per Section:
-20.00/+20.00 percent single section
Case Material:
Metal
Capacitive Electrode Material:
Tantalum
Power Factor At Reference Tempurature In Percent:
10.0000
Dc Leakage At Reference Temp:
8.000 microamperes
Terminal Surface Treatment:
Solder

Terminal Type And Quantity: 2 uninsulated wire lead

NSN 5910-00-683-3049

Electrolytic Fixed Capacitor - Page 2 of 2



_					
c	hο	JIF.		.ife:	
J			_	.II C.	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0