NSN 5910-00-683-3060

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-683-3060
Body Style:
W/o mtg facilities, axial terminals
Reliability Indicator:
Not established
Terminal Length:
Between 1.625 inches and 2.625 inches
Body Diameter:
Between 0.188 inches and 0.208 inches
Body Length:
Between 0.781 inches and 0.843 inches
Terminal Diameter:
0.020 inches
Schematic Diagram Designator:
No common or grounded electrode (s)
Features Provided:
Hermetically sealed case
Capacitance Value Per Section:
0.010 microfarads single section
Nonderated Operating Temp:
Between -55.0 degrees celsius and 85.0 degrees celsius
Between -55.0 degrees celsius and 85.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section:
Nonderated Continuous Voltage Rating And Type Per Section:
Nonderated Continuous Voltage Rating And Type Per Section: 400.0 dc single section
Nonderated Continuous Voltage Rating And Type Per Section: 400.0 dc single section Tolerance Range Per Section:
Nonderated Continuous Voltage Rating And Type Per Section: 400.0 dc single section Tolerance Range Per Section: -10.00/+10.00 percent single section
Nonderated Continuous Voltage Rating And Type Per Section: 400.0 dc single section Tolerance Range Per Section: -10.00/+10.00 percent single section Case Material:
Nonderated Continuous Voltage Rating And Type Per Section: 400.0 dc single section Tolerance Range Per Section: -10.00/+10.00 percent single section Case Material: Metal
Nonderated Continuous Voltage Rating And Type Per Section: 400.0 dc single section Tolerance Range Per Section: -10.00/+10.00 percent single section Case Material: Metal Insulation Resistance At Reference Temp:
Nonderated Continuous Voltage Rating And Type Per Section: 400.0 dc single section Tolerance Range Per Section: -10.00/+10.00 percent single section Case Material: Metal Insulation Resistance At Reference Temp: 50000.0 megohm-microfarads
Nonderated Continuous Voltage Rating And Type Per Section: 400.0 dc single section Tolerance Range Per Section: -10.00/+10.00 percent single section Case Material: Metal Insulation Resistance At Reference Temp: 50000.0 megohm-microfarads Dissipation Factor At Reference Tempurature In Percent:
Nonderated Continuous Voltage Rating And Type Per Section: 400.0 dc single section Tolerance Range Per Section: -10.00/+10.00 percent single section Case Material: Metal Insulation Resistance At Reference Temp: 50000.0 megohm-microfarads Dissipation Factor At Reference Tempurature In Percent: 1.500
Nonderated Continuous Voltage Rating And Type Per Section: 400.0 dc single section Tolerance Range Per Section: -10.00/+10.00 percent single section Case Material: Metal Insulation Resistance At Reference Temp: 50000.0 megohm-microfarads Dissipation Factor At Reference Tempurature In Percent: 1.500 Terminal Surface Treatment:
Nonderated Continuous Voltage Rating And Type Per Section: 400.0 dc single section Tolerance Range Per Section: -10.00/+10.00 percent single section Case Material: Metal Insulation Resistance At Reference Temp: 50000.0 megohm-microfarads Dissipation Factor At Reference Tempurature In Percent: 1.500 Terminal Surface Treatment: Solder
Nonderated Continuous Voltage Rating And Type Per Section: 400.0 dc single section Tolerance Range Per Section: -10.00/+10.00 percent single section Case Material: Metal Insulation Resistance At Reference Temp: 50000.0 megohm-microfarads Dissipation Factor At Reference Tempurature In Percent: 1.500 Terminal Surface Treatment: Solder Dielectric Material:
Nonderated Continuous Voltage Rating And Type Per Section: 400.0 dc single section Tolerance Range Per Section: -10.00/+10.00 percent single section Case Material: Metal Insulation Resistance At Reference Temp: 50000.0 megohm-microfarads Dissipation Factor At Reference Tempurature In Percent: 1.500 Terminal Surface Treatment: Solder Dielectric Material: Plastic polyester
Nonderated Continuous Voltage Rating And Type Per Section: 400.0 dc single section Tolerance Range Per Section: -10.00/+10.00 percent single section Case Material: Metal Insulation Resistance At Reference Temp: 50000.0 megohm-microfarads Dissipation Factor At Reference Tempurature In Percent: 1.500 Terminal Surface Treatment: Solder Dielectric Material: Plastic polyester Terminal Type And Quantity:
Nonderated Continuous Voltage Rating And Type Per Section: 400.0 dc single section Tolerance Range Per Section: -10.00/+10.00 percent single section Case Material: Metal Insulation Resistance At Reference Temp: 50000.0 megohm-microfarads Dissipation Factor At Reference Tempurature In Percent: 1.500 Terminal Surface Treatment: Solder Dielectric Material: Plastic polyester Terminal Type And Quantity: 2 uninsulated wire lead
Nonderated Continuous Voltage Rating And Type Per Section: 400.0 dc single section Tolerance Range Per Section: -10.00/+10.00 percent single section Case Material: Metal Insulation Resistance At Reference Temp: 50000.0 megohm-microfarads Dissipation Factor At Reference Tempurature In Percent: 1.500 Terminal Surface Treatment: Solder Dielectric Material: Plastic polyester Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life:

No

Demilitarization:

NSN 5910-00-683-3060

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 2 of 2



Fiig:

A010b0