NSN 5910-00-683-3337

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-683-3337 **Body Style:** W/thd bushing mtg, terminal (s) on one end Reliability Indicator: Not established **Body Diameter:** 1.375 inches **Body Length:** 2.250 inches **Schematic Diagram Designator:** No common or grounded electrode (s) **Anode Type:** Plain foil **Impedance At Minimum Operating Tempurature In Ohms:** 1480.0 **Electrical Polarization:** Polarized **Mounting Facility Screw Thread Series Designator:** Un **Mounting Facility Type And Quantity:** 1 threaded bushing **Features Provided:** Mounting hardware **Capacitance Value Per Section:** 10.000 microfarads single section **Nonderated Operating Temp:** Between -40.0 degrees celsius and 85.0 degrees celsius **Thread Size:** 0.875 inches Nonderated Continuous Voltage Rating And Type Per Section: 400.0 dc single section **Tolerance Range Per Section:** -10.00/+50.00 percent single section **Case Material:** Metal **Capacitive Electrode Material:** Aluminum

Dissipation Factor At Reference Tempurature In Percent: 17.0000 Dc Leakage At Reference Temp:

94.000 microamperes

Terminal Surface Treatment:

Solder

NSN 5910-00-683-3337

Electrolytic Fixed Capacitor - Page 2 of 2



| Terminal Type | And | Quantity: |
|---------------|-----|-----------|
|---------------|-----|-----------|

2 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0