## NSN 5910-00-683-6828

Glass Dielectric Variable Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-683-6828 **Body Style:** Piston **Terminal Length:** 1.500 inches **Bushing Diameter:** 0.257 inches **Shaft Diameter:** 0.257 inches single shaft **Bushing Length:** 0.250 inches **Shaft Length:** 0.625 inches single shaft **Body Length:** 1.031 inches **Overall Diameter:** 0.812 inches Tempurature Coefficient Of Capacitance In Ppm Per Deg Celsius: 0.0 single section **Tolerance Of Tempurature Coefficient In Ppm Per Deg Celsius:** -100.0/+100.0 single section **Terminal Diameter:** 0.025 inches **Mounting Facility Screw Thread Series Designator:** Unef **Inclosure Type:** Encased **Adjustment Device Torque:** Between 1.000 inch-ounces and 10.000 inch-ounces **Bushing Shape:** Round w/flat Insulation Dc Resistance At 25 Deg Celsius: 1000.0 gigohms **Bushing Width:** 0.237 inches **Mounting Facility Type And Quantity:** 1 threaded bushing **Nonderated Operating Temp:** Between -55.0 degrees celsius and 125.0 degrees celsius **Thread Size:** 

0.250 inches

**Capacitance Range In Picofarads:** 

+1.0/+16.0 single section

## NSN 5910-00-683-6828

Fiig: A096a0

Glass Dielectric Variable Capacitor - Page 2 of 2



Nonderated Voltage Rating And Type:
500.0 dc continuous single section
Adjustment Device Drive Type And Quantity:
1 slotted screw
Capacitance Drift In Picofarads:
0.04 single section
Material:
Glass insulation supporting
Test Data Document:
81349-mil-c-14409 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Terminal Type And Quantity:
1 wire lead
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No