NSN 5910-00-683-7364

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-683-7364

view Online at https://aerobasegroup.com/nsn/5910-00-663-7364	
Body Style:	
W/mtg bracket, axial terminals	
Reliability Indicator:	
Not established	
Terminal Length:	
0.296 inches	
Body Diameter:	
0.562 inches	
Body Length:	
1.124 inches	
Continuous Current Rating In Amps:	
1.0	
Unthreaded Mounting Hole Diameter:	
0.156 inches	
Schematic Diagram Designator:	
No common or grounded electrode (s)	
Mounting Facility Type And Quantity:	
1 unthreaded mounting holes	
Features Provided:	
Hermetically sealed case	
Insulation Resistance At Maximum Operating Temp:	
10.0 megohm-microfarads	
Capacitance Value Per Section:	
1.000 microfarads single section	
Nonderated Operating Temp:	
Between -55.0 degrees celsius and 125.0 degrees celsius	
Nonderated Continuous Voltage Rating And Type Per Section	12
200.0 dc single section	
Tolerance Range Per Section:	
-10.00/+10.00 percent single section	
Case Material:	
Metal	
Insulation Resistance At Reference Temp:	
2000.0 megohm-microfarads	
Power Factor At Reference Tempurature In Percent:	
1.0000	
Terminal Surface Treatment:	
Solder	
Terminal Type And Quantity:	
2 tab, solder lug	
Short Lito.	

N/a

NSN 5910-00-683-7364

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 2 of 2



		• -						
	In		Of	RЛ	മാ	CI	ır	Δ.
L	,,,			IVI	ca			

--

Demilitarization:

No

Fiig:

A010b0