

View Online at https://aerobasegroup.com/nsn/5910-00-688-5846

## Body Style:

W/thd mtg studs, axial terminals

### **Reliability Indicator:**

Not established

## **Terminal Length:**

1.625 inches

### Body Diameter:

1.000 inches

#### **Body Length:**

1.884 inches

## Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

1.125 inches

### Schematic Diagram Designator:

No common or grounded electrode (s)

## Mounting Facility Screw Thread Series Designator:

Unc

## Mounting Facility Type And Quantity:

2 threaded mounting studs

#### **Features Provided:**

Hermetically sealed case

# Insulation Resistance At Maximum Operating Temp:

40.0 megohm-microfarads

#### Capacitance Value Per Section:

2.000 microfarads single section

#### Nonderated Operating Temp:

Between -55.0 degrees celsius and 125.0 degrees celsius

#### Thread Size:

0.138 inches

# Nonderated Continuous Voltage Rating And Type Per Section:

400.0 dc single section

#### **Tolerance Range Per Section:**

-10.00/+10.00 percent single section

#### **Case Material:**

Metal

#### Insulation Resistance At Reference Temp:

2000.0 megohm-microfarads

# Power Factor At Reference Tempurature In Percent:

1.0000

## **Terminal Surface Treatment:**

Solder

#### **Terminal Type And Quantity:**

2 uninsulated wire lead

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 2 of 2



Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0