

View Online at https://aerobasegroup.com/nsn/5910-00-688-6283

## **Body Style:**

W/o mtg facilities, axial terminals

**Reliability Indicator:** 

Not established

**Terminal Length:** 

1.625 inches

**Body Diameter:** 

0.312 inches

**Body Length:** 

0.875 inches

**Body Width:** 

0.312 inches

Body Height:

0.312 inches

**Terminal Diameter:** 

0.025 inches

## Schematic Diagram Designator:

No common or grounded electrode (s)

## **Internal Electrical Connection Type:**

Extended foil

## **Features Provided:**

Hermetically sealed case

## Insulation Resistance At Maximum Operating Temp:

150.0 megohms

### Capacitance Value Per Section:

4700.000 picofarads single section

### Nonderated Operating Temp:

Between -55.0 degrees celsius and 125.0 degrees celsius

## Nonderated Continuous Voltage Rating And Type Per Section:

600.0 dc single section

### **Tolerance Range Per Section:**

-10.00 to 10.00 percent single section

#### **Case Material:**

Metal

### Insulation Resistance At Reference Temp:

18000.0 megohms

## **Dissipation Factor At Reference Tempurature In Percent:**

1.0000

# **Terminal Surface Treatment:**

Solder

### **Test Data Document:**

81349-mil-c-25 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).



# Terminal Type And Quantity:

2 uninsulated wire lead

# Specification Data:

81349-mil-c-25/1k government specification

Shelf Life:

N/a

# Unit Of Measure:

---

# Demilitarization:

No

Fiig:

A010b0