

View Online at https://aerobasegroup.com/nsn/5910-00-688-6328

## **Body Style:**

W/o mtg facilities, radial terminals

# **Reliability Indicator:**

Not established

# Body Diameter:

0.255 inches

#### Body Length:

0.505 inches

## **Terminal Height From Body:**

1.312 inches

## Schematic Diagram Designator:

No common or grounded electrode (s)

## Insulation Resistance At Maximum Operating Temp:

1000.0 megohms

## **Capacitance Value Per Section:**

51.000 picofarads single section

## **Nonderated Operating Temp:**

Between -55.0 degrees celsius and 125.0 degrees celsius

## Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius:

-150.0 single section

## Nonderated Continuous Voltage Rating And Type Per Section:

500.0 dc single section

## Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius:

-30.0/+30.0 single section

#### **Tolerance Range Per Section:**

-2.00/+2.00 percent single section

### Case Material:

Ceramic

Insulation Resistance At Reference Temp:

50000.0 megohms

# Quality Factor At Reference Temp:

1000.0000

# **Terminal Surface Treatment:**

Solder

# Test Data Document:

81349-mil-c-20 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

# Terminal Type And Quantity:

2 uninsulated wire lead

## Shelf Life:

N/a

Unit Of Measure:



Demilitarization:

No

Fiig:

A010b0