## NSN 5910-00-690-1616

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-690-1616

**Body Style:** W/o mtg facilities, axial terminals **Reliability Indicator:** Not established **Terminal Length:** 1.500 inches **Body Diameter:** 0.135 inches **Body Length:** 0.286 inches **Schematic Diagram Designator:** No common or grounded electrode (s) **Anode Type:** Solid **Electrical Polarization:** Polarized **Features Provided:** Hermetically sealed case **Capacitance Value Per Section:** 0.100 microfarads single section **Nonderated Operating Temp:** Between -55.0 degrees celsius and 85.0 degrees celsius Dc Leakage At Maximum Operating Temp: 6.3 milliamperes Nonderated Continuous Voltage Rating And Type Per Section: 75.0 dc single section **Tolerance Range Per Section:** -10.00/+10.00 percent single section **Case Material:** Metal **Capacitive Electrode Material: Dissipation Factor At Reference Tempurature In Percent:** 2.0000 Dc Leakage At Reference Temp: 0.500 microamperes **Terminal Surface Treatment:** Solder **Test Data Document:** 

81439-milc39003/1 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification

format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain

environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## Terminal Type And Quantity:

2 uninsulated wire lead

## NSN 5910-00-690-1616

Electrolytic Fixed Capacitor - Page 2 of 2



_					
c	hο	JIF.		.ife:	
J			_	.II C.	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0