

View Online at <https://aerobasegroup.com/nsn/5910-00-702-5655>

**Body Style:**

W/mtg tabs/flanges terminal (s) on one surface

**Reliability Indicator:**

Not established

**Mounting Slot Width:**

0.156 inches

**Body Length:**

1.750 inches

**Body Width:**

0.640 inches

**Body Height:**

2.000 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:**

2.125 inches

**Schematic Diagram Designator:**

One terminal common to each section

**Mounting Facility Type And Quantity:**

1 mounting slots

**Section Quantity:**

2

**Features Provided:**

Hermetically sealed case

**Insulation Resistance At Maximum Operating Temp:**

20.0 megohm-microfarads

**Capacitance Value Per Section:**

0.500 microfarads all sections

**Nonderated Operating Temp:**

Between -55.0 degrees celsius and 85.0 degrees celsius

**Nonderated Continuous Voltage Rating And Type Per Section:**

600.0 dc all sections

**Tolerance Range Per Section:**

-10.00 to 10.00 percent 2nd section

**Case Material:**

Metal

**Insulation Resistance At Reference Temp:**

2000.0 megohm-microfarads

**Dissipation Factor At Reference Temperature In Percent:**

1.0000

**Terminal Surface Treatment:**

Solder

**Special Features:**

Section 1 terminal 2 to terminal 1; section 2 terminal 3 to terminal 1

**Test Data Document:**

81349-mil-c-25 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Terminal Type And Quantity:**

3 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A010b0