## NSN 5910-00-706-9983

Plastic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-706-9983 **Body Style:** W/mtg bracket, terminal (s) on one end **Reliability Indicator:** Not established **Terminal Length:** 0.485 inches **Body Diameter:** 1.000 inches **Body Length:** 2.125 inches **Unthreaded Mounting Hole Diameter:** 0.156 inches **Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:** 0.750 inches **Schematic Diagram Designator:** No common or grounded electrode (s) **Mounting Facility Type And Quantity:** 2 unthreaded mounting holes **Insulation Resistance At Maximum Operating Temp:** 500.0 megohms **Capacitance Value Per Section:** 0.270 microfarads single section **Nonderated Operating Temp:** Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 280.0 ac-rms single section **Tolerance Range Per Section:** -5.00/+5.00 percent single section **Case Material:** Metal **Insulation Resistance At Reference Temp:** 150000.0 megohms **Dissipation Factor At Reference Tempurature In Percent:** 1.000 **Dielectric Material:** Plastic polyethylene terephthalate and plastic polytetrafluoroethylene **Terminal Type And Quantity:** 2 tab, solder lug Shelf Life: N/a

--

**Unit Of Measure:** 

## NSN 5910-00-706-9983

Plastic Dielectric Fixed Capacitor - Page 2 of 2



Demilitarization:

No

Fiig:

A010b0