NSN 5910-00-709-9883

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-709-9883

view Offiline at https://acrobasegroup.com/histi/03/10-00-703-3003
Body Style:
W/o mtg facilities, axial terminals
Reliability Indicator:
Not established
Terminal Length:
1.625 inches
Body Diameter:
Between 1.000 inches and 1.016 inches
Body Length:
Between 2.562 inches and 2.593 inches
Terminal Diameter:
0.025 inches
Schematic Diagram Designator:
No common or grounded electrode (s)
Features Provided:
Hermetically sealed case
Insulation Resistance At Maximum Operating Temp:
20.0 megohm-microfarads
Capacitance Value Per Section:
18.000 microfarads single section
Nonderated Operating Temp:
Between -55.0 degrees celsius and 85.0 degrees celsius
Nonderated Continuous Voltage Rating And Type Per Section:
150.0 dc single section
Tolerance Range Per Section:
-20.00/+20.00 percent single section
Case Material:
Metal
Insulation Resistance At Reference Temp:
2000.0 megohm-microfarads
Power Factor At Reference Tempurature In Percent:
1.000
1.000
1.000 Terminal Surface Treatment:
1.000 Terminal Surface Treatment: Solder
1.000 Terminal Surface Treatment: Solder Terminal Type And Quantity:
1.000 Terminal Surface Treatment: Solder Terminal Type And Quantity: 2 uninsulated wire lead
1.000 Terminal Surface Treatment: Solder Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life:
1.000 Terminal Surface Treatment: Solder Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: N/a

No

NSN 5910-00-709-9883

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 2 of 2



Fiig:

A010b0