NSN 5910-00-713-4192

Glass Dielectric Variable Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-713-4192 **Body Style:**

Piston

Overall Length:

1.261 inches

Shaft Diameter:

0.120 inches single shaft

Shaft Length:

0.105 inches single shaft

Body Length:

1.156 inches

Overall Diameter:

0.312 inches

Tempurature Coefficient Of Capacitance In Ppm Per Deg Celsius:

0.0 single section

Tempurature Coefficient Of Capacitance Range In Ppm Per Deg Celsius:

-100.0/+100.0 single section

Center To Center Distance Between Terminals Parallel To Length:

1.000 inches

Center To Center Distance Between Terminals Parallel To Diameter:

Between 0.235 inches and 0.275 inches

Quality Factor At 25 Deg Celsius:

500.0

Inclosure Type:

Encapsulated

Adjustment Device Torque:

Between 1.000 inch-ounces and 10.000 inch-ounces

Insulation Dc Resistance At 25 Deg Celsius:

1.0 gigohms

Mounting Facility Type And Quantity:

4 terminal

Nonderated Operating Temp:

Between -55.0 degrees celsius and 125.0 degrees celsius

Shaft Type:

Round, slotted single shaft

Capacitance Range In Picofarads:

+1.0/+21.0 single section

Nonderated Voltage Rating And Type:

750.0 dc continuous single section

Adjustment Device Drive Type And Quantity:

1 shaft

Capacitance Drift In Picofarads:

0.04 single section

NSN 5910-00-713-4192

Glass Dielectric Variable Capacitor - Page 2 of 2



Terminal Type And Quantity:
4 wire lead
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A096a0