## NSN 5910-00-717-3883

**Body Style:** 

W/thd mtg studs, axial terminals

**Schematic Diagram Designator:** 

**Reliability Indicator:** 

Not established

Terminal Length:

1.625 inches **Body Diameter:**0.670 inches **Body Length:**1.562 inches

0.875 inches

Paper Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-717-3883

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

Electrod (s) grounded to case, w/gnd terminal
Internal Electrical Connection Type:
Extended foil
Mounting Facility Screw Thread Series Designator:
Unc
Mounting Facility Type And Quantity:
2 threaded mounting studs
Features Provided:
Hermetically sealed case
Capacitance Value Per Section:
1.000 microfarads single section
Nonderated Operating Temp:
Between -55.0 degrees celsius and 85.0 degrees celsius
Thread Size:
0.138 inches
Nonderated Continuous Voltage Rating And Type Per Section:
100.0 dc single section
Tolerance Range Per Section:
-10.00 to 10.00 percent single section
Case Material:
Metal
Insulation Resistance At Reference Temp:
18000.0 megohms
Dissipation Factor At Reference Tempurature In Percent:
1.0000
Terminal Type And Quantity:
2 uninsulated wire lead
Shelf Life:
N/a

## NSN 5910-00-717-3883

Paper Dielectric Fixed Capacitor - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A010b0