## NSN 5910-00-720-9986

**Body Style:** 

Plastic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-720-9986

W/o mtg facilities, terminal (s) on one surface
Reliability Indicator:
Not established
Body Length:
2.500 inches
Body Width:
1.188 inches
Body Height:
3.500 inches
Schematic Diagram Designator:
No common or grounded electrode (s)
Features Provided:
Hermetically sealed case
Insulation Resistance At Maximum Operating Temp:
300.0 megohm-microfarads
Capacitance Value Per Section:
4.000 microfarads single section
Nonderated Operating Temp:
Between -65.0 degrees celsius and 85.0 degrees celsius
Nonderated Continuous Voltage Rating And Type Per Section:
600.0 dc single section
Tolerance Range Per Section:
-10.00/+10.00 percent single section
Case Material:
Metal
Insulation Resistance At Reference Temp:
15000.0 megohm-microfarads
Dissipation Factor At Reference Tempurature In Percent:
1.0000
Terminal Surface Treatment:
Solder
Test Data Document:
81349-mil-c-19978 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). And 81349-mil-c-19978/3
specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes
commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and
performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Terminal Type And Quantity:
2 tab, solder lug
Shelf Life:
N/a

**Unit Of Measure:** 

## NSN 5910-00-720-9986

Plastic Dielectric Fixed Capacitor - Page 2 of 2



Fiig:

A010b0