

View Online at <https://aerobasegroup.com/nsn/5910-00-721-2048>

**Body Style:**

W/thd mtg hol (s)/stud(s) terminal(s) on one surface

**Reliability Indicator:**

Not established

**Terminal Length:**

0.875 inches

**Body Length:**

4.938 inches

**Body Width:**

1.500 inches

**Body Height:**

4.750 inches

**Center To Center Distance Between Terminals Parallel To Length:**

1.000 inches

**Terminal Diameter:**

0.164 inches

**Terminal Height From Body:**

0.500 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:**

4.000 inches

**Schematic Diagram Designator:**

No common or grounded electrode (s)

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

0.750 inches

**Mounting Facility Screw Thread Series Designator:**

Unc

**Mounting Facility Type And Quantity:**

4 threaded mounting studs

**Section Quantity:**

2

**Features Provided:**

Hermetically sealed case

**Insulation Resistance At Maximum Operating Temp:**

450.0 megohms

**Capacitance Value Per Section:**

5.000 microfarads 2nd section

**Nonderated Operating Temp:**

Between -55.0 degrees celsius and 85.0 degrees celsius

**Thread Size:**

0.190 inches

**Nonderated Continuous Voltage Rating And Type Per Section:**

1000.0 dc 2nd section

**Tolerance Range Per Section:**

-15.00 to 15.00 percent 2nd section

**Case Material:**

Metal

**Insulation Resistance At Reference Temp:**

4500.0 megohms

**Dissipation Factor At Reference Temperature In Percent:**

1.0000

**Test Data Document:**

81349-mil-c-25/14 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Terminal Type And Quantity:**

2 threaded stud

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A010b0