NSN 5910-00-723-6974

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-723-6974
Body Style:
W/o mtg facilities, axial terminals
Reliability Indicator:
Not established
Terminal Length:
1.500 inches
Body Diameter:
Between 0.890 inches and 0.922 inches
Body Length:
Between 0.937 inches and 1.063 inches
Terminal Diameter:
0.025 inches
Schematic Diagram Designator:
Electrod (s) grounded to case, w/gnd terminal
Anode Type:
Etched foil
Impedance At Minimum Operating Tempurature In Ohms:
392.0
Electrical Polarization:
Nonpolarized
Capacitance Value Per Section:
4.000 microfarads single section
Nonderated Operating Temp:
Between -55.0 degrees celsius and 85.0 degrees celsius
Dc Leakage At Maximum Operating Temp:
38.0 microamperes
Nonderated Continuous Voltage Rating And Type Per Section:
100.0 dc single section
Tolerance Range Per Section:
-15.00/+30.00 percent single section
Case Material:
Metal
Capacitive Electrode Material:
Tantalum
Dc Leakage At Reference Temp:
7.000 microamperes
Terminal Surface Treatment:
Solder
Case Insulation Material:
Plastic

Terminal Type And Quantity:

2 uninsulated wire lead

NSN 5910-00-723-6974

Electrolytic Fixed Capacitor - Page 2 of 2



_				
c	hο	JIF.		ife:
J	116		_	HG.

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0