Paper Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-724-5967

## **Body Style:**

W/o mtg facilities, terminal (s) on one surface

## **Reliability Indicator:**

Not established

## **Body Length:**

4.562 inches

### **Body Width:**

3.750 inches

## **Body Height:**

6.000 inches

### Center To Center Distance Between Terminals Parallel To Length:

2.000 inches

**Terminal Height From Body:** 

2.750 inches

#### Schematic Diagram Designator:

No common or grounded electrode (s)

### Internal Electrical Connection Type:

Extended foil

### **Features Provided:**

Hermetically sealed case

## Insulation Resistance At Maximum Operating Temp:

10.0 megohms

#### Capacitance Value Per Section:

0.500 microfarads single section

#### Nonderated Operating Temp:

Between -55.0 degrees celsius and 85.0 degrees celsius

#### Nonderated Continuous Voltage Rating And Type Per Section:

7500.0 dc single section

#### **Tolerance Range Per Section:**

-10.00 to 10.00 percent single section

#### **Case Material:**

Metal

## Insulation Resistance At Reference Temp:

6000.0 megohms

## Dissipation Factor At Reference Tempurature In Percent:

1.0000

## **Terminal Surface Treatment:**

Solder

### **Test Data Document:**

81349-mil-c-25/7d specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

# Terminal Type And Quantity:

2 solder stud

Paper Dielectric Fixed Capacitor - Page 2 of 2

AeroBase Group

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A010b0