

View Online at <https://aerobasegroup.com/nsn/5910-00-725-0676>

Body Style:

W/thd mtg bushing, terminals on opposite ends

Reliability Indicator:

Not established

Width Across Flats:

0.312 inches

Terminal Length:

0.250 inches

Body Length:

0.750 inches

Schematic Diagram Designator:

Feedthrough

Mounting Facility Screw Thread Series Designator:

Unf

Mounting Facility Type And Quantity:

1 threaded bushing

Capacitance Value Per Section:

4000.000 picofarads single section

Nonderated Operating Temp:

Between -55.0 degrees celsius and 85.0 degrees celsius

Thread Size:

0.250 inches

Temperature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius:

-1400.0 single section

Nonderated Continuous Voltage Rating And Type Per Section:

500.0 dc single section

Tolerance Of Temperature Coefficient Per Section In Ppm Per Deg Celsius:

-0.025/+0.025 single section

Tolerance Range Per Section:

-20.00/+20.00 percent single section

Case Material:

Metal

Power Factor At Reference Temperature In Percent:

2.5000

Quality Factor At Reference Temp:

335.0000

Terminal Surface Treatment:

Solder

Precious Material And Location:

Bushing surfaces silver

Terminal Type And Quantity:

1 solder stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0