## NSN 5910-00-725-3168

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-725-3168

view Online at https://acrobasegroup.com/nsi//0310-00-723-0100
Body Style:
W/o mtg facilities terminal (s) on one surface
Reliability Indicator:
Not established
Terminal Length:
1.000 inches
Body Length:
0.585 inches
Body Width:
0.700 inches
Body Height:
0.310 inches
Center To Center Distance Between Terminals Parallel To Length:
0.450 inches
Terminal Diameter:
0.025 inches
Schematic Diagram Designator:
No common or grounded electrode (s)
Capacitance Value Per Section:
0.220 microfarads single section
Nonderated Operating Temp:
Between -40.0 degrees celsius and 85.0 degrees celsius
Nonderated Continuous Voltage Rating And Type Per Section:
50.0 dc single section
Tolerance Range Per Section:
-10.00/+10.00 percent single section
Case Material:
Plastic
Insulation Resistance At Reference Temp:
500.0 megohm-microfarads
Dissipation Factor At Reference Tempurature In Percent:
1.500
Terminal Surface Treatment:
Solder
Dielectric Material:
Plastic polyethylene terephthalate
Terminal Type And Quantity:
2 uninsulated wire lead
Shelf Life:
N/a

**Unit Of Measure:** 

## NSN 5910-00-725-3168

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 2 of 2



	tariz	

No

Fiig:

A010b0