## NSN 5910-00-725-7229

Glass Dielectric Variable Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-725-7229 **Thread Class:** 2a **Body Style:** Piston **Bushing Diameter:** 0.250 inches **Bushing Length:** 0.250 inches **Body Length:** 0.464 inches **Overall Diameter:** 0.312 inches Tempurature Coefficient Of Capacitance Range In Ppm Per Deg Celsius: -50.0/+50.0 single section **Quality Factor At 25 Deg Celsius:** 500.0 **Mounting Facility Screw Thread Series Designator:** Unef **Inclosure Type: Encased Bushing Shape:** Round w/flat Insulation Dc Resistance At 25 Deg Celsius: 1000.0 gigohms **Bushing Width:** 0.225 inches **Mounting Facility Type And Quantity:** 1 threaded bushing **Nonderated Operating Temp:** Between -55.0 degrees celsius and 125.0 degrees celsius **Thread Size:** 0.250 inches Capacitance Range In Picofarads: +1.0/+14.0 single section **Nonderated Voltage Rating And Type:** 1000.0 dc continuous single section **Adjustment Device Drive Type And Quantity:** 1 slotted screw **Test Data Document:** 

24930-g320028s4 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing,

etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Terminal Type And Quantity:

1 tab, solder lug and 1 turret

## NSN 5910-00-725-7229

Glass Dielectric Variable Capacitor - Page 2 of 2



Shelf Life:
-------------

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A096a0