NSN 5910-00-725-7233

Paper Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-725-7233 **Body Style:** W/thd bushing mtg, terminals on opposite ends Reliability Indicator: Not established **Terminal Length:** 1.625 inches **Body Diameter:** 0.400 inches **Body Length:** 0.771 inches **Body Width:** 0.400 inches **Body Height:** 0.400 inches **Schematic Diagram Designator:** No common or grounded electrode (s) **Internal Electrical Connection Type:** Inserted tab **Mounting Facility Screw Thread Series Designator:** Unf **Mounting Facility Type And Quantity:** 1 threaded bushing **Features Provided:** Mounting hardware and hermetically sealed case **Insulation Resistance At Maximum Operating Temp:** 150.0 megohms **Capacitance Value Per Section:** 10000.000 picofarads single section **Nonderated Operating Temp:** Between -55.0 degrees celsius and 125.0 degrees celsius **Thread Size:** 0.312 inches Nonderated Continuous Voltage Rating And Type Per Section: 400.0 dc single section **Tolerance Range Per Section:** -10.00 to 10.00 percent single section **Case Material:** Metal

Insulation Resistance At Reference Temp:

18000.0 megohms

Dissipation Factor At Reference Tempurature In Percent:

1.0000

NSN 5910-00-725-7233

Paper Dielectric Fixed Capacitor - Page 2 of 2



		T 4 4
ı ermına	i Surtace	Treatment:

Solder

Test Data Document:

81349-mil-c-25 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

2 uninsulated wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0