

View Online at <https://aerobasegroup.com/nsn/5910-00-725-8396>

Body Style:

W/o mtg facilities, axial terminals

Mil-std-1276 Wire Lead Type Designator:

N-1

Reliability Indicator:

Not established

Terminal Length:

1.500 inches

Body Diameter:

0.351 inches

Body Length:

0.786 inches

Schematic Diagram Designator:

Electrod (s) grounded to case, w/gnd terminal

Anode Type:

Solid

Electrical Polarization:

Polarized

Features Provided:

Hermetically sealed case

Capacitance Value Per Section:

150.000 microfarads single section

Nonderated Operating Temp:

Between -55.0 degrees celsius and 85.0 degrees celsius

Dc Leakage At Maximum Operating Temp:

250.0 milliamperes

Nonderated Continuous Voltage Rating And Type Per Section:

15.0 dc single section

Tolerance Range Per Section:

-10.00/+10.00 percent single section

Case Material:

Metal

Capacitive Electrode Material:

Tantalum

Dissipation Factor At Reference Temperature In Percent:

8.0000

Dc Leakage At Reference Temp:

20.000 microamperes

Terminal Surface Treatment:

Solder

Case Insulation Material:

Plastic

Test Data Document:

10001-2557744 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Terminal Type And Quantity:

2 uninsulated wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0