

View Online at <https://aerobasegroup.com/nsn/5910-00-725-9000>

**Body Style:**

W/mtg tabs/flanges, terminal (s) on one surface

**Reliability Indicator:**

Not established

**Body Length:**

2.625 inches

**Body Width:**

2.125 inches

**Body Height:**

2.750 inches

**Maximum Rf Current Rating At Highest Rated Frequency In Rms Amps:**

10.0

**Highest Frequency At Which Rf Current Rating Applies In Kilohertz:**

15000.0

**Maximum Rf Current Rating At Lowest Rated Frequency In Rms Amps:**

15.0

**Lowest Frequency At Which Rf Current Rating Applies In Kilohertz:**

1875.0

**Unthreaded Mounting Hole Diameter:**

0.281 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:**

3.250 inches

**Schematic Diagram Designator:**

No common or grounded electrode (s)

**Mounting Facility Type And Quantity:**

2 unthreaded mounting holes

**Features Provided:**

Hermetically sealed case

**Capacitance Value Per Section:**

10000.000 picofarads single section

**Nonderated Operating Temp:**

Between -55.0 degrees celsius and 85.0 degrees celsius

**Nonderated Continuous Voltage Rating And Type Per Section:**

7000.0 dc 2nd section

**Tolerance Range Per Section:**

-20.00 to 20.00 percent single section

**Case Material:**

Ceramic

**Terminal Type And Quantity:**

2 solder stud

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A010b0