

View Online at <https://aerobasegroup.com/nsn/5910-00-725-9000>

Body Style:

W/mtg tabs/flanges, terminal (s) on one surface

Reliability Indicator:

Not established

Body Length:

2.625 inches

Body Width:

2.125 inches

Body Height:

2.750 inches

Maximum Rf Current Rating At Highest Rated Frequency In Rms Amps:

10.0

Highest Frequency At Which Rf Current Rating Applies In KiloHertz:

15000.0

Maximum Rf Current Rating At Lowest Rated Frequency In Rms Amps:

15.0

Lowest Frequency At Which Rf Current Rating Applies In KiloHertz:

1875.0

Unthreaded Mounting Hole Diameter:

0.281 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

3.250 inches

Schematic Diagram Designator:

No common or grounded electrode (s)

Mounting Facility Type And Quantity:

2 unthreaded mounting holes

Features Provided:

Hermetically sealed case

Capacitance Value Per Section:

10000.000 picofarads single section

Nonderated Operating Temp:

Between -55.0 degrees celsius and 85.0 degrees celsius

Nonderated Continuous Voltage Rating And Type Per Section:

7000.0 dc 2nd section

Tolerance Range Per Section:

-20.00 to 20.00 percent single section

Case Material:

Ceramic

Terminal Type And Quantity:

2 solder stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0