## NSN 5910-00-726-3598

Plastic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-726-3598

**Body Style:** W/mtg tabs/flanges, terminal (s) on one surface Reliability Indicator: Not established **Mounting Slot Width:** 0.187 inches **Body Length:** 3.060 inches **Body Width:** 2.870 inches **Body Height:** 1.620 inches Center To Center Distance Between Terminals Parallel To Length: Between 1.380 inches and 1.620 inches **Terminal Height From Body:** 0.750 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: Between 3.625 inches and 3.685 inches **Schematic Diagram Designator:** No common or grounded electrode (s) **Internal Electrical Connection Type:** Extended foil **Mounting Facility Type And Quantity:** 2 mounting slots **Features Provided:** Hermetically sealed case **Capacitance Value Per Section:** 4.000 microfarads single section **Nonderated Operating Temp:** Between -55.0 degrees celsius and 55.0 degrees celsius Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius: -100.0 single section Nonderated Continuous Voltage Rating And Type Per Section: 200.0 dc single section **Tolerance Range Per Section:** -0.50/+0.50 percent single section **Case Material:** Metal

**Insulation Resistance At Reference Temp:** 

10.0 megohms

**Dissipation Factor At Reference Tempurature In Percent:** 

0.1000

NSN 5910-00-726-3598 Plastic Dielectric Fixed Capacitor - Page 2 of 2



Terminal Surface Treatment:
Solder
Dielectric Material:
Plastic polystyrene
Terminal Type And Quantity:
2 solder stud
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A010b0