## NSN 5910-00-726-5029

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-726-5029

Body Style:					
W/thd bushing mtg, terminal (s) on one end					
Reliability Indicator:					
Not established					
Terminal Length:					
0.296 inches					
Body Diameter:					
0.500 inches					
Body Length:					
1.094 inches					
Schematic Diagram Designator:					
Electrod (s) grounded to case					
Mounting Facility Screw Thread Series Designator:					
Unf					
Mounting Facility Type And Quantity:					
1 threaded bushing					
Features Provided:					
Hermetically sealed case					
Insulation Resistance At Maximum Operating Temp:					
40.0 megohm-microfarads					
•					
Capacitance Value Per Section:					
0.150 microfarads single section					
Nonderated Operating Temp:					
Between -55.0 degrees celsius and 125.0 degrees celsius  Thread Size:					
0.312 inches					
Nonderated Continuous Voltage Rating And Type Per Section:					
400.0 dc single section					
Tolerance Range Per Section:					
-20.00/+20.00 percent single section					
Case Material:					
Metal					
Insulation Resistance At Reference Temp:					
· ·					
2000.0 megohm-microfarads  Power Factor At Reference Tempurature In Percent:					
1.0000 Terminal Surface Treatment:					
Solder Terminal Type And Quantity:					
Terminal Type And Quantity:					
1 tab, solder lug					
Shelf Life:					

N/a

## NSN 5910-00-726-5029

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 2 of 2



ш	Inıt	· / 1+	Measure	

--

Demilitarization:

No

Fiig:

A010b0