NSN 5910-00-726-5030

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-726-5030

Body Style:							
W/thd bushing mtg, terminal (s) on one end							
Reliability Indicator:							
Not established							
Terminal Length:							
0.296 inches							
Body Diameter:							
0.312 inches							
Body Length:							
1.062 inches							
Schematic Diagram Designator:							
Electrod (s) grounded to case							
Mounting Facility Screw Thread Series Designator:							
Unf							
Mounting Facility Type And Quantity:							
1 threaded bushing							
Features Provided:							
Hermetically sealed case							
Insulation Resistance At Maximum Operating Temp:							
10.0 megohm-microfarads							
Capacitance Value Per Section:							
0.150 microfarads single section							
Nonderated Operating Temp:							
Between -55.0 degrees celsius and 125.0 degrees celsius							
Thread Size:							
0.312 inches							
Nonderated Continuous Voltage Rating And Type Per Section:							
200.0 dc single section							
Tolerance Range Per Section:							
-20.00/+20.00 percent single section							
Case Material:							
Metal							
Insulation Resistance At Reference Temp:							
2000.0 megohm-microfarads							
2000.0 megohm-microfarads Power Factor At Reference Tempurature In Percent:							
•							
Power Factor At Reference Tempurature In Percent:							
Power Factor At Reference Tempurature In Percent: 1.0000							
Power Factor At Reference Tempurature In Percent: 1.0000 Terminal Surface Treatment:							
Power Factor At Reference Tempurature In Percent: 1.0000 Terminal Surface Treatment: Solder							

N/a

NSN 5910-00-726-5030

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 2 of 2



		• -						
	In		Of	RЛ	മാ	CI	ır	Δ.
L	,,,			IVI	ca			

--

Demilitarization:

No

Fiig:

A010b0