## NSN 5910-00-726-5049

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-726-5049 **Body Style:** W/mtg bracket, terminal (s) on one end **Reliability Indicator:** Not established **Terminal Length:** 0.296 inches **Body Diameter:** 0.400 inches **Body Length:** 0.812 inches **Unthreaded Mounting Hole Diameter:** 0.144 inches **Schematic Diagram Designator:** Electrod (s) grounded to case **Mounting Facility Type And Quantity:** 1 unthreaded mounting holes **Features Provided:** Hermetically sealed case **Insulation Resistance At Maximum Operating Temp:** 10.0 megohm-microfarads **Capacitance Value Per Section:** 0.220 microfarads single section **Nonderated Operating Temp:** Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 200.0 dc single section **Tolerance Range Per Section:** -20.00/+20.00 percent single section Case Material: Metal **Insulation Resistance At Reference Temp:** 2000.0 megohm-microfarads **Power Factor At Reference Tempurature In Percent:** 1.0000 **Terminal Surface Treatment:** Solder **Terminal Type And Quantity:** 1 tab, solder lug Shelf Life:

Shelf Life: N/a Unit Of Measure:

## NSN 5910-00-726-5049

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 2 of 2



_		••	• -				
1	em		ゖっ	riz	<b>2</b> †1	n	
_			ıιa	114	au	VII	١.

No

Fiig:

A010b0