

View Online at https://aerobasegroup.com/nsn/5910-00-726-5984

#### **Body Style:**

W/thd mtg bushing, terminals on opposite ends

**Reliability Indicator:** 

Not established

## Width Across Flats:

0.250 inches

#### **Terminal Length:**

0.250 inches

#### **Body Length:**

0.468 inches

## **Terminal Diameter:**

0.051 inches

## Schematic Diagram Designator:

#### Feedthrough

#### Mounting Facility Screw Thread Series Designator:

Unf

# Mounting Facility Type And Quantity:

1 threaded bushing

# **Capacitance Value Per Section:**

1000.000 picofarads single section

## Voltage Tempurature Limits Per Section In Percent Capacitance Change:

-66.0 to 22.0 without voltage applied single section

#### Nonderated Operating Temp:

Between -55.0 degrees celsius and 85.0 degrees celsius

#### **Thread Size:**

0.216 inches

#### Nonderated Continuous Voltage Rating And Type Per Section:

500.0 dc single section

#### **Tolerance Range Per Section:**

-0.00 to 100.00 percent single section

#### **Case Material:**

Metal

# Insulation Resistance At Reference Temp:

7500.0 megohms

# Power Factor At Reference Tempurature In Percent:

2.5000

# **Terminal Surface Treatment:**

Solder

# **Terminal Type And Quantity:**

2 uninsulated wire lead

# Shelf Life:

N/a



Unit Of Measure:

---

Demilitarization:

No

Fiig:

A010b0